

Dealer Price List 2007 - 340mm, IMO X-Band RADAR (25kW)

| Product Description | Product Code | Q'ty | List Price |
|---------------------|--------------|------|------------|
|---------------------|--------------|------|------------|

IMO X-BAND RADAR (340mm)



Model: JMA-9900 Series with ARPA

2 Unit Type, X-Band Up-Mast

Model: JMA-9922-6XA (Stand-alone type)

JMA-9922-6XA 1 set

Model: JMA-9922F-6XA (Desk-top type)

JMA-9922F-6XA 1 set

23.1" LCD Color Display with ARPA

25kW Up-Mast, 6ft Scanner, 50 Target ARPA



***** Desk Top version available by special order only**

1 Set consists of:

| | | | |
|-------------------------------|-----------------------------|---------------|-----|
| 25kW Transceiver, 6ft Scanner | With Performance Monitor | NKE-1087-6 | (1) |
| 23.1" Color TFT LCD Display | | NCD-4263 | (1) |
| AIS Interface Unit | | NQA-4172 | (1) |
| Scanner Cable | 37m (121.4') Cable, 14-core | 2695110056-37 | (1) |
| Standard Spare Parts | | 7ZXR00016 | (1) |
| Installation Accessories | For Display Unit | MPXP33029 | (1) |
| Installation Manual (English) | | 7ZPRD0608 | (1) |
| Instruction Manual (English) | | 7ZPRD0606 | (1) |

Options - RADAR JMA-9900 Series :

| | | | |
|-------------------------------|----------------------------------|---------------|----------|
| VDR Connection Kit | | CQD-1891 | 1 |
| Interswitch Unit | Max. 2 Radars | NQE-3141-2 | 1 |
| Interswitch Unit | Max. 4 Radars | NQE-3141-4 | 1 |
| Interswitch Cable | 10m (32.8') Cable | 269111153-10M | 1 |
| Log Book | | 6ZPRD00003 | 1 |
| Display Cover | Vinyl | MPXM33089 | 1 |
| Power Converter/Amplifier | For cable runs over 65m (213.2') | NQE-3155 | 1 |
| Simulator | Including CFQ-8879 Cable | NDW-51 | 1 |
| Simulator Cable | | CFQ-8879 | 1 |
| Installation Manual (English) | | 7ZPRD0608 | 1 |
| Instruction Manual (English) | | 7ZPRD0606 | 1 |
| Anti-Ice Kit | Special Order Only ** | | 1 |

**** Anti-ice kit must be installed at time of manufacture.**

Dealer Price List 2007 - 340mm, IMO X-Band RADAR (25kW)

| Product Description | Product Code | Q'ty | List Price |
|---------------------|--------------|------|------------|
|---------------------|--------------|------|------------|

Power Requirements:

100 / 110 / 115 VAC, 50/60 Hz, Single-phase, 800VA
 200 / 230 VAC, 50/60 Hz, Single or Three-phase, 800VA

Shipping Weights & Dimensions - JMA-9922-6XA:

| | | | |
|-------------|--------------------|---------|---|
| Display | 48"L x 30"W x 49"H | 550 lbs | 1 |
| Scanner | 84"L x 24"W x 30"H | 132 lbs | 1 |
| Cable | 24"L x 17"W x 13"H | 21 lbs | 1 |
| Accessories | 19"L x 13"W x 14"H | 8 lbs | 1 |

Notes:

If ship's main power source is 440VAC, a step-down transformer shall be used.

Supplied as standard for EITHER 110 VAC, single-phase OR 220VAC, single-phase; to be specified when ordering.

220 VAC, three-phase is also available as a special order.

Certifications:

| | | |
|-------------------------|-----------------------|---------------------|
| QinetiQ MED Certificate | QQ-MED-11/04-02R | Valid: 1 April 2009 |
| * USCG Certificate | 165.120ECO191/2304-02 | Valid: 1 April 2009 |
| FCC Certificate | CKE-NKE-1087 | |
| Russian Type Approval | 05.02761.011 | Valid: 1 July 2008 |

* ARPA function only

Dealer Price List 2007 - 340mm, IMO X-Band RADAR (25kW)

| Product Description | Product Code | Q'ty | List Price |
|---------------------|--------------|------|------------|
|---------------------|--------------|------|------------|

